



CONTACT US

PRONTOTEC ITALIA SRL

Via Dell'Artigianato, 6
36070 Brogliano (VI)
ITALY

marketing@prontotec.it

PBA2000

SOFTCOVER SOLUTION

Prontotec
EUROPEAN ENGINEERING

TECNICAL DETAILS

Compact and simple to use
Cover feeder with double sheets
Safety barrier system included
Touch screen for main function
Hotmelt Glue system integrated
Exist with belt
Not required a specialized operator
Diagnostic control from remote

Technical Details

Max. Book Block Size: 440x280 (mm)
Min. Book Block Size: 230x120 (mm)
Max. Cover Size: 430x770 (mm)
Min Cover Size: 100x230 (mm)
Min Book Thickness: 3 (mm)
Max Book Thickness: 70 (mm)
Max. Mechanical Speed: 1.800(c/h)
Cover Weight Range: 82 to 300 gsm
Glue Temperature: 170°C
Side Glue Tank: 4 Kg
Main Power: 20 (kw),
380-400V, 3 Phase, 50 Hz
Net Weight: 4000(kg)
Overall Dimensions:
(L*W*H) 4500x1450x1450(mm)

PERFECT BINDER SOLUTION

PBA2000 is a three clamps perfect binder. After data input,unites automatic adjustment as below: · Spine milling station, width automatic adjustment. · Notching station, width automatic adjustment. · Side glue station, width automatic adjustment.And It is automatic spine glue cut-off. · Cover guides on the cover feeder,width automatic adjustment. · Scoring width automatic adjustment. · Cover guides(both front and side) on the nipping table,width automatic adjustment. · Book block width between nipping plates automatic adjustment. With the main characters such as Stepless-speed regulation, PLC program control, PIO temperature control ,automatic detectors, overload protector, etc, it is an ideal equipment for flexible and quick binding of small and medium book quantities.

